



3799 Commerce Rd
 London . Ontario
 Canada . N6N 1P9
 Toll Free: 1-888-689-0683
 Local: 1-519-644-2444
 Fax: 1-519-644-2520
 email: harring@harringdoors.com

45 Minute Positive/Negative Pressure - Glass Doors

Opening Sizes	Minimum	Maximum
Singles		3/6 X 8/0
Singles		4/0 X 7/0
Pairs Note: Pairs allowed with or without metal astragal.		7/0 X 8/0
Allowable Species	Any standard species	
Thickness	1 3/4"	2 1/4"
Dimensions		
Stile Face	6"	
Top Rail Face	6"	
Bottom Rail Face	10"	
Lites		
Single Lite Size - Wire Glass - Ceramic		1296 sq.ins. 1444 sq.ins.
Hardware (must be rated)		
Cylinder Locks	6" min. stile face	
Mortise Locks	6" min. stile face	
Minimum Latch Throw	1/2" singles/ 3/4" pairs	
Dead Bolts	6" min. stile face	
Automatic Flush Bolts	6" min. stile face	
Manual Flush Bolts - standard and extension	6" min. stile face	
Surface Vertical Rods	6" min. stile face	
Rim Exit Device	6" min. stile face	
Auto Door Bottom		Label type only
Wire Raceway		3/8" X 3/8"

UBC 7-2 1997 Positive Pressure Doors (smoke & draft control)

All of the above specifications are allowed, however we must be notified if the doors will be used in a **positive pressure** application.

NOTE: Positive pressure doors must be installed in strict compliance to Harring Doors installation instructions for 45 minute positive pressure doors. All doors were tested under the Warnock Hersey Label.