



3799 Commerce Rd
 London . Ontario
 Canada . N6N 1P9
 Toll Free: 1-888-689-0683
 Local: 1-519-644-2444
 Fax: 1-519-644-2520
 email: harring@harringdoors.com

60 Minute Positive/Negative Pressure - Panel Doors

OPENING SIZES	MINIMUM	MAXIMUM
Singles		3/6 X 8/0
Singles		4/0 x 7/0
Pairs NOTE: Pairs allowed with or without metal astragal.		7/0 X 8/0
ALLOWABLE SPECIES	Any standard species	
THICKNESS	1 3/4"	2 1/4"
DIMENSIONS		
Stile Face	6"	
Top Rail Face	6"	
Bottom Rail Face	10"	
PANELS		
Thickness - Raised	1 5/8"	2752 sq. ins.
Thickness - Flat	5/8"	2752 sq. ins.
HARDWARE (Must be rated)		
Cylinder Locks	6" min. stile face	
Mortise Locks	6" min. stile face	
Minimum Latch Throw	1/2" singles /3/4" pairs	
Dead Bolts	6" min. stile face	
Automatic Flush Bolts	6" min. stile face	
Manual Flush Bolts – standard and extension	6" min. stile face	
Surface Vertical Rods	6" min. stile face	
Rim Exit Device	6" min. stile face	
Auto Door Bottom		Label type only
Wire Raceway		3/8" x 3/8"

UBC 7-2 1997 Positive Pressure Doors (smoke & draft control)

All of the above specifications are allowed, however we must be notified if the doors will be used in a **positive pressure** application.

NOTE: Positive pressure doors must be installed in strict compliance to Harring Doors installation instructions for 60 minute positive pressure doors. All doors were tested under the Warnock Hersey Label.